



Eclipse Series

## ERS200A

All Wood • For Pocket Insert • Double Hung Window With Square Frame, Arched Sash

### PRODUCT SPECIFICATIONS

#### FRAME

---

- Head, jamb and sill frame parts are constructed of kiln dried ponderosa pine, treated with a water repellent preservative to protect from rot and insects. Optional mahogany available.
- Blindstop, sill, exterior grilles and optional screenstop are also available in cPVC in addition to pine (standard) or mahogany.
- Head and jamb wood joints are tenoned, glued and nailed.
- Frame thickness:  $1\frac{1}{16}$ " at jamb and head.
- Standard jamb depth:  $4\frac{5}{8}$ "; (With optional screenstop:  $5\frac{1}{8}$ ")
- Sill is  $\frac{1}{2}$ " thick on a 9 degree angle and is designed for a sash pocket type installation from the exterior (existing blindstop may need to be trimmed). Exterior window height is  $1\frac{3}{16}$ " greater than interior.
- Available with optional  $\frac{3}{8}$ " foam wrap for air tight installation.
- A continuous sill (up to 120") is used on mulled units.

#### SASH

---

- Sashes are of kiln dried ponderosa pine, treated with a water repellent preservative. Optional mahogany available.
- Sash joints are tenoned, glued and nailed from the interior.
- Silicone glazed from the interior for a positive water tight seal.
- Overall finish sash thickness:  $1\frac{7}{16}$ " (standard), optional  $1\frac{3}{4}$ " sash available.
- Sash profile widths are: stiles ( $1\frac{3}{4}$ " ), top rail ( $2\frac{5}{8}$ " ), meeting rails ( $1\frac{7}{16}$ " ) and bottom rail ( $3\frac{1}{4}$ " ). Optional 4" bottom rail available.
- Unequal sash heights can be specified.
- Top and bottom operating sashes with locking pivot shoe tilt-in and can be removed for finishing or cleaning.

#### EXTERIOR FINISH

---

- Standard factory primed white in pine (standard) or mahogany.
- Available in unfinished natural wood or prefinished white in pine (standard) or mahogany. Contact Trimline dealer for custom color details.
- Blindstop, sill, exterior grilles and optional screenstop are also available in cPVC in addition to pine (standard) or mahogany. Sash are of pine (standard) or mahogany.

#### INTERIOR FINISH

---

- Standard in unfinished natural wood in specified species (pine (standard) or mahogany) which can be painted or stained.
- Available factory primed or prefinished white in pine (standard) or mahogany. Contact Trimline dealer for custom color details.
- Interior features a concealed jambliner giving the appearance of a traditional wood window.

#### HARDWARE

---

- Combination locking and tilting hardware system. Tilt feature is activated via an internal tie-bar mechanism concealed within the lower meeting rail eliminating the need for surface mounted tilt latches providing a cleaner, more traditional appearance.
- Dual locks standard on units under 28" wide; triple locks standard on units over 50" wide. Sash lifts standard at bottom rail.
- All hardware components are of zinc alloy in matching finish available in: beige, white, oil rubbed bronze and satin nickel.

#### BALANCE SYSTEM

---

- Concealed block and tackle system for smooth and effortless operation with locking cam action pivot shoes that never needs adjusting. AAMA 902-07 tested for over 28,000 cycles without failure.

#### WEATHERSTRIPPING

---

- Head, meeting rails and bottom rail are weather sealed with Q-Lon® almond color compression seal foam; Fin-Seal® at the sill dam.
- Vertical stiles are sealed via Q-Lon® foam compression seal inserted into a flexible t-slot which is integral to the jambliner. Flexible T-slot assists the compression seal substantially in compensating for any "bowing" occurring during installation.

#### GLASS

---

- Standard clear  $1\frac{1}{16}$ " thick insulating glass, consisting of "double strength" 3 mm annealed glass,  $\frac{7}{16}$ " air space using Tremco's EnerEDGE® warm-edge, dual-seal silicone foam spacer, hermetically sealed with hot melt butyl.
- All insulating glass units meet IGMA and NFRC 706 requirements for seal durability and gas retention per ASTM E2190, E2188-10 & E2189-10.

- Other glazing options Comfort E and Comfort E Plus Low E with argon gas, obscure, tempered, laminated, bronze or grey tint. Decorative glass also available.

## INSECT SCREENS

- Standard half screen of .050" thick extruded aluminum.
- Optional full screen of .019" thick roll-formed aluminum.
- Optional interior sliding half screen of .050" thick extruded aluminum. (Requires 5" jamb pocket.)
- Standard colors available: white, bronze, earthtone, beige, black and hunter green. Custom colors also available.
- Charcoal fiberglass screen cloth (18 x 16 mesh) standard; optional screen mesh available in charcoal or aluminum color wire or Better View™ high transparency screening in charcoal fiberglass cloth only.

## GRILLES

- **Simulated Divided Lites (SDL)** in a classic putty glazed 5/8", 7/8", 1", 1 1/4" or 1 1/2" wood (optional cPVC) muntin profile permanently applied to exterior of the insulated glass. Double faced tape is used to apply muntin to the glass which first is prepared with a saline type glass bonding and coupling agent before muntin is applied to help ensure lasting adhesion. An optional between the glass dark bronze shadow bar is available for an authentic true divided lite look. Interior wood in pine (standard) or mahogany matching the interior wood species in either permanent or removable style 5/8" or 7/8" wide divided lite patterns only. Removable style not available in 1", 1 1/4", 1 1/2" widths.
- **True Divided Lites (TDL):** Available in 1 1/8" width in pine only. TDL bar has the look of historically accurate true putty glazing.
- **Removable wood grilles** available in 5/8" or 7/8" wide classic double stepped profile matching window interior wood species in pine (standard) or mahogany in a wide array of standard or custom divided lite patterns only.
- **In-glass aluminum "GBG"** (Grille Between the Glass) muntins are available in 5/8" flat profile or 7/8" sculptured profile in all standard exterior cladding color finishes for dust free easy cleaning. Available in either divided lite or diamond patterns.
- **Combo wood-aluminum:** 5/8" flat or 3/4" sculptured in-glass aluminum muntin with either permanently applied (see SDL) or removable wooden interior wood grille in pine (standard) or mahogany.

## ACCESSORIES

- A standard zero clearance mullion is used for factory mulling of windows without increasing the combined unit dimension of the windows mulled.
- Interior wooden mullion covers in pine (standard) or mahogany are provided loose.
- 1 1/16" interior wooden jamb extension in pine (standard) or mahogany are factory applied to the perimeter of the window and are available in custom sizes to provide an overall jamb depth up to 9".

## WARRANTY

- Limited 10 year.
- 20 years non-prorated on insulating glass.
- Non-square, decorative/leaded glass 5 years.

## PERFORMANCE

### Thermal Ratings

Glazing	U-Value	R-Value	SHGC	VT	CRF
Comfort E	.28	3.57	.28	.50	57
Comfort E Plus	.25	4.00	.27	.49	47

Comfort E – 3mm RLE CS-36 (#2) / Clear / Argon

Comfort E Plus – 3 mm RLE CS-36 (#2) / CS-72 (#4) / Argon

SHGC = Solar Heat Gain Coefficient

VT = Visible Transmittance

### Structural Ratings

Test Speciman	Air Infiltration	Performance Class-Grade
44.0" x 75.75" (1118 mm x 1924 mm)	.14 cfm/ft <sup>2</sup>	LC-40

## TEST STANDARDS

- NFRC certified: meets or exceeds rating and labeling requirements as per NFRC 100, 200 and 500 test procedures.
- AMMA/WDMA/CSA 101/I.S.2/A440-05
- ENERGY STAR® certified